

HANVO GENERAL HANDLING PU GLOVE



EN388:2016



MECHANICAL RISK PROFILE

Performance against mechanical risk tests as stipulated by the EN388 standard.

| | | | | | |
|-------------|---|---|---|---|---|
| ABRASION | 1 | 2 | 3 | 4 | |
| CUT | 1 | 2 | 3 | 4 | 5 |
| TEAR | 1 | 2 | 3 | 4 | |
| PENETRATION | 1 | 2 | 3 | 4 | |

POLYURETHANE COATING PROPERTIES

Polyurethane is a thermosetting polymer that forms a thin coating with low particle shed. It's flexibility offers superior dexterity and good grip.

| | | | | | |
|------------|---|---|---|---|---|
| DRY GRIP | 1 | 2 | 3 | 4 | 5 |
| WET GRIP | 1 | 2 | 3 | 4 | 5 |
| OIL GRIP | 1 | 2 | 3 | 4 | 5 |
| DEXTERITY | 1 | 2 | 3 | 4 | 5 |
| DURABILITY | 1 | 2 | 3 | 4 | 5 |
| DIVERSITY | 1 | 2 | 3 | 4 | 5 |

SPECIFICATIONS

- Seamless 13 gauge black woven nylon liner provides increased comfort, dexterity and breathability.
- Polyurethane (PU) palm coating provides excellent abrasion & tear resistance without compromising tactile sensitivity.
- Knit wrist helps prevent dust & debris from entering the glove liner.
- Washable to extend the glove life and reduce replacement costs.
- Breathable back for comfort.
- Sizes: 8/M, 9/L, 10/XL, 11/XXL.
- Dimensions (+/-5%): 255mm x 102mm x 36g.
- Packaging: Individually packaged pairs, 12 pairs per bag, 120 pairs per carton.

FEATURES

- | | | |
|-------------|----------------------|-----------|
| Strong Grip | Flexible | Light |
| Breathable | Ergonomically Shaped | Soft Feel |

APPLICATIONS

- | | | |
|--------------------------|-------------------------|-------------------------|
| Automotive | General Duty | Gardening / Agriculture |
| Assembly / Manufacturing | Transport / Warehousing | |