

FLUXS3SMID

Lightweight comfortable and metal-free S3S mid-cut

FLUX S3S LOW delivers durable, water-resistant protection with a breathable upper, lightweight metal-free safety and a strong grip for light industrial work.

Upper	TPU, Synthetic Nubuck
Lining	Recycled Mesh
Footbed	SJ Memory foam footbed
Midsole	Anti-puncture Textile
Outsole	PU/PU
Toecap	Nano Carbon
Category	S3S / SR, SC, FO, ESD, CI
Size range	EU 35-50 / UK 3.0-14.0 / US 3.0-15.0 JPN 21.5-33.0 / KOR 230-330
Sample weight	0.568 kg
Norms	EN ISO 20345:2022+A1:2024 ASTM F2413:2024



BI K



Metal free

Metal free safety shoes are in general lighter than regular safety shoes. They are also very beneficial for professionals who have to pass through metal detectors several times a day.



Slip resistance (SR)

Replaces the previously used term of SRA+SRB=SRC. SR means the slip test has been executed on tiles contaminated with soap and with oil.



Electrostatic Discharge (ESD)

ESD provides the controlled discharge of electrostatic energy that can damage electronic components and avoids risks of ignition resulting from electrostatic charges. Volume resistance between 100 KiloOhm and 100 MegaOhm.



Scuff Cap (SC)

Separately tested material to cover the toe cap area to reduce abrasion of the upper material (e.g. during kneeling operations) and extend usability of the safety shoe.



Breathable upper

Increased moisture and temperature management for extended wearer comfort.



Nano carbon toecap

Ultralight high-tech material, metal-free with no thermal or electrical conductivity.

Industries:
Construction, Assembly, Automotive, Catering, Cleaning, Food & beverages, Industry, Logistics

Environments:
Dry environment, Extreme slippery surfaces, Uneven surfaces, Wet environment

Maintenance instructions:
To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

	Description	Measure unit	Result	EN ISO 20345
Upper	TPU, Synthetic Nubuck			
	Upper: permeability to water vapor	mg/cm ² /h	2.3	≥ 0.8
	Upper: water vapor coefficient	mg/cm ²	19.9	≥ 15
Lining	Recycled Mesh			
	Lining: permeability to water vapor	mg/cm ² /h	49.8	≥ 2
	Lining: water vapor coefficient	mg/cm ²	398.8	≥ 20
Footbed	SJ Memory foam footbed			
	Footbed: abrasion resistance (dry/wet) (cycles)	cycles	Dry 25600 cycles/Wet 12800 cycles	25600/12800
Outsole	PU/PU			
	Outsole abrasion resistance (volume loss)	mm ³	40.9	≤ 150
	Basic Slip resistance - Ceramic + NaLS - Forward heel slip	friction	0.49	≥ 0.31
	Basic Slip resistance - Ceramic + NaLS - Backward forepart slip	friction	0.48	≥ 0.36
	SR Slip resistance - Ceramic + glycerin - Forward heel slip	friction	0.30	≥ 0.19
	SR Slip resistance - Ceramic + glycerin - Backward forepart slip	friction	0.25	≥ 0.22
	Antistatic value	MegaOhm	18.7	0.1 - 1000
	ESD value	MegaOhm	5.2	0.1 - 100
	Heel energy absorption	J	30	≥ 20
Toecap	Nano Carbon			
	Impact resistance toecap (clearance after impact 100J)	mm	N/A	N/A
	Compression resistance toecap (clearance after compression 10kN)	mm	N/A	N/A
	Impact resistance toecap (clearance after impact 200J)	mm	15.5	≥ 14
	Compression resistance toecap (clearance after compression 15kN)	mm	21.5	≥ 14

Sample size: 42

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.