Flagship of Simon Shoes with Advanced Technology **8611 BLACK** 8600 SERIES





Good Design

Last shape for good holding

Good hold on the instep.

Luxury Genuine Leather

Using the high quality and soft genuine leather

Wide type ACM resin toecap

Lightweight and toughness

Non-Hydrolyzable midsole

Strong for long-term storage Uses "SX high-performance resin".

Stumbling prevention design

Enough Toe spring







Cradle-like comfort

Excellent cushioning and hold "Cradle in-sock" that disperses foot pressure. (Antibacterial and deodorant processing)

Designed to prevent liquid ingress

A "protect line" that prevents liquid from entering through the joint between the instep and sole.

Anti-slip and safety performance

Excellent slip resistance, JIS standard Clears anti-slip category 2 (F2). JIS T 8101 safety shoes CI / S / P1 / F2 / HI1 / H passed







Obtained patent Patent No. 5851480, 6046020, 6195884

For various work scenes for JIS safety Responding comfort, cushioning, and high functionality plus. Patent No. 5851480



*Customers are responsible for connection and communication charges.



Shock absorption

Patent No.6046020

A suspension system that absorbs obstacles and bumps on the road surface to help walking. Achieve higher stability in the optimization of the hardness balance of the rubber.



Slip resistance

[S-shaped block pattern] By increasing the cleats to which foot pressure is applied when walking, slip resistance and stability are provided.

Patent No.6195884



Stability

A flat sole makes a large ground contact area and excellent stability.



Flexible sole

Excellent flexibility makes Light footwork.



Oil resistance, chemical resistance, High temperature heat resistance

Uses oil- and chemical-resistant materials * 1.

Also, Clears the standard for "Heat insulation of sole complex" category 1 (HI1) that protects the feet.

Main Spec: ● Standard: JIS T 8101 Safety Shoe C I /S/P1/F2/HI1/H ● Size (EEE)/Code: 23.5~28.0cm(1706060) ● Upper: High grade Leather (Soft)

• Toecap: Wide Composite (ACM) • Outsole: SX 3 Layer Fsole (SX PU+2Layer SX Rubber) • Insock: Cradle Insole • Weight: 820g (26.0cm/pair)

Certification: Certified Factory of ISO 14001, ISO 45001