Simon Star series

SS11 BLACK



Last shape for good holding

Good hold on the instep.

Wide type ACM resin toecap

Lightweight and toughness

Designed to prevent liquid ingress

A "protect line" that prevents liquid from entering through the joint between the instep and sole.

Non-Hydrolyzable midsole

Strong for long-term storage Uses "SX high-performance resin".

Stumbling prevention design

Enough Toe spring







Cradle-like comfort

Excellent cushioning and hold "Cradle in-sock" that disperses foot pressure. (Antibacterial and deodorant processing)

Soft comfort

Easy to wear and soft to wear. "Top line cushion".

Anti-slip and safety performance

Excellent slip resistance, JIS standard Clears anti-slip category 1 (F1).

JIS T 8101 safety shoes C I /S/P1/F1 passed



SX3層底SSy-n

Obtained patent Patent No. 5851480、6195884

For various work scenes for JIS safety Responding comfort, cushioning, and high functionality plus. Patent No. 5851480



Shock absorption

A suspension system that absorbs obstades and bumps on the road surface to help walking. Achieve higher stability in the optimization of the hardness balance of the rubber.

Patent No.6046020



Slip resistance

[S-shaped block pattern]
By increasing the deats to which
foot pressure is applied when
walking, slip resistance and stability
are provided.

Patent No.6195884



Stability

A flat sole makes a large ground contact area and excellent stability.



Flexible sole

Excellent flexibility makes Light footwork.



Oil resistance, chemical resistance, High temperature heat resistance

Uses oil- and chemical-resistant materials * 1.

Also, Clears the standard for "Heat insulation of sole complex" category 1 (HI1) that protects the feet.

Main Specifications: ●Norm: JIS T 8101 safety shoes C I /S/P1/F1 passed

• Size(EEE)/Product code: 23.5~28.0cm(1523350),29.0 (1523352) · 30.0cm(1523359)

● Upper: Cowhide (Embossed soft)+mesh ● Toe cap: Non-metallics ● Sole: SX Triple Layer SS sole(PU + Rubber)

● In-sock: Cradle in-sock (EVA + Knitting textile) ● Standard weight: 840g(26.0cm/Pair)

● Notices: ISO 14001, OHSAS18001Manufactured at a certified factory