
Combustible Cabinet

WA810450R



















It has acquired FM & CE Certification and is in strict comply with FM Approval Standard for Storage Cabinets (Flammable and Combustible Liquids) Class Number 6050, OSHA 29 CER 1910.106 of American Occupational Safety and Health Administration, NFPA CODE30 of American National Fire Protection Association and Hazardous Chemicals Control Ordinance of State Bureau of Safe Production Supervision and Administration

SYSBEL Combustible Cabinets for storing paintings, oil and other flammable liquids(high flash point liquid, flash point≥37.8°C), Suitable for coating, printing, furniture, automobile and other industries.

- 1.Double-wall construction with 38mm insulating air space for fire resistance.
- 2. Over 1.2mm thick, fully welded, construction holds squareness for longer life, offering greater
- 3.5.3cm leak tight sump at the bottom of cabinet's maximally catches incidental drips.
- 4.Door can be fully opened to 180°, easy to operate, three-point latch with a manual lock for better
- 5. Standardized warning label is highly visible and anti-corrosive.
- 6. Unique spill-catcher shelves catch incidental drips and adjust on 6cm centers.
- 7. Durable&chemical resistant, lead-free powder coat inside and outside cabinet, reduce effects of corrosion and humidity.
- 8.2inches vents with integral flame arresters in both sides of every cabinet.
- 9.In terms of OSHA, on outside side panel, there is built-in grounding static connector for easy grounding.



	Combustible Cabinet WA810450R									
•	Volume (Gal/L)	Certification	Door type	Ext dimension (H×W×D/cm)	Packing dimension (H×W×D/cm)	Adjustable Shelves(Pcs)	Shelf Loading Weight(Kgs.)	N.W. (Kgs.)	G.W. (Kgs.)	Model
	45/170	FM, CE	Double Door/ Manual	165x109x46	182x120x57	2	100	114	133	WA810450R

WA810450R





Product details



18Ga(1-mm)quality galvanized steel Unleaded coating with polish surface, which is corrosion and moisture proof




Fireproofing vents to effectively reduce the concentration of volatile substances, and prevent fire hazards. Special spill-proof shelves to avoid chemical leakage by accident.



The cabinet has three-point linkage lock, and the door can open 180°
Two person management in line with Hazardous Chemicals Control Ordinance (December 1st, 2011 Version)



The three-point bullets: Anti-static design structure





Shelf bracket welded on both sides of cabinet



FM Approved Anti-Static Device:Conductor grip combine the equipment with the cabinet to conduct the static to earth, thus to prevent fire accident



SYSBEL

