## Safety Containers SYSBEL Oily Waste Cans

WA8109100






## **SYSBEL Oily Waste Cans**

A good helper for you to connect oily trashes!

In order to prevent fire risks and collect rags and cloth submersed in oil (flammable solvents, linseed oil and other flammable liquids), please use OSHA standard oily waste can. SYSBEL oily waste can has special lid whose opening angle is no more than 60 degree. The self-closing lid design ensures the can tightly closed in the absence of external force, to effectively control the three elements of fires \*.



Heat (or ignition source)

Heat (or ignition source): mechanical electrostatic line damaged, a lighted match or sparked cigarettes, etc

Oxygen: oxygen of air

Fuel: flammable and combustible liquids, such as diesel kerosene, gasoline, etc

Туре	For Type			
Oily Waste Can	Flashing point≤80o F(27 oC) Trash immersed in flammable liquids			





SYSBEL Oily Waste Cans						
Capacity(Gal/L)	Ext. Dimensions(H×D/cm)	Packing Dimensions(H×W×D/ cm)	N.W. (Kgs.)	G.W.(Kgs.)	Model	
6/22.6	40x30	46x42x42	4.5	6	WA8109100	



## The oily waste can plays an important role!

- 1. Pedal switch control, requiring no manual operation
- 2. Unique body and base design of the can to effectively reduce t he possibility of fire
- 3. Maximum lid opening angle is 60 degrees, in accordance with Underwriters Laboratories (UL) safety standards
- 4. Scope: Red products for tarnish flammable liquid waste; yellow for tarnish combustible liquid waste
- \*Please refer to P10 for the three elements of fire



0