

# Drench Hose

**WG7011R**



It complies with the regulations in ANSI Z358.1-2014 standard and OSHA 29 CFR 1910.151(C) issued by ANSI has acquired CE Certification

Drench hose units, WG7011R & WG7012R are for deck mounting. Ideal for rinsing any part of user's eye, face or body. Under ANSI Z358.1-2014, drench hose units supplement, but do not replace, other types of emergency equipment.

- To meet the standard of Emergency Eyewash and Shower Equipment in ANSI Z358.1-2014 and AS4775-2007;
- Single or double spray head is optional, which has dust cover;
- Forged brass squeeze valve activated by plastic lever handle. Valve has replaceable stainless steel seat for exceptional durability. Valve closes when lever handle is released.
- 1.5m soft PVC tube wrapped by PE film relief from rust and leakage, and internal filter to remove impurities from the water flow.
- Spray heads provide even, continued and comfortable fluid to irrigate the eye;
- Eye wash exceeds minimum water flow of 0.4GPM(1.5LPM) at 210kPa (30psi);
- Deck flange for countertop mounting, flange has a position to fix the unit.

### Portable Eyewash with Mobile Waste Cart

Product	Main Material	Color	Flow Speed (L/min)	Inlet & Outlet	Pressure (KPa)	Packing size L*W*H/cm	G.W. (kgs.)	Model
Drench Hose	304SS	Red	6L/min	G1/2	3-6bar	27.4*19.6*15.6	1.4	<b>WG7011R</b>

