

Drench Hose

WG7012R



It complies with the regulations in ANSI Z358.1-2014 standard and OSHA 29 CFR 1910.151(C) issued by ANSI has acquired CE Certification

Drench hose units, WG7011R & WG7012R are for deck mounting. Ideal for rinsing any part of user's eye, face or body. Under ANSI Z358.1-2014, drench hose units supplement, but do not replace, other types of emergency equipment.

- To meet the standard of Emergency Eyewash and Shower Equipment in ANSI Z358.1-2014 and AS4775-2007;
- Single or double spray head is optional, which has dust cover;
- Forged brass squeeze valve activated by plastic lever handle. Valve has replaceable stainless steel seat for exceptional durability. Valve closes when lever handle is released.
- 1.5m soft PVC tube wrapped by PE film relief from rust and leakage, and internal filter to remove impurities from the water flow.
- Spray heads provide even, continued and comfortable fluid to irrigate the eye;
- Eye wash exceeds minimum water flow of 0.4GPM(1.5LPM) at 210kPa (30psi);
- Deck flange for countertop mounting, flange has a position to fix the unit.

Portable Eyewash with Mobile Waste Cart

| Product | Main Material | Color | Flow Speed (L/min) | Inlet & Outlet | Pressure (KPa) | Packing size L*W*H/cm | G.W. (kgs.) | Model |
|-------------|---------------|-------|--------------------|----------------|----------------|-----------------------|-------------|----------------|
| Drench Hose | 304SS | Red | 10L/min | G1/2 | 3-6bar | 27. 4*19. 6*15. 6 | 1. 6 | WG7012R |

