

ZEUS CI K702 TECHNICAL DATA SHEET

PRODUCT NO.	K702
PRODUCT NAME	ZEUS S3 CI

DESCRIPTION
BOOTS BROWN COLOR STEEL TOECAP AND INSERT PLATE NO.905 DUEL DENSITY PU OUTSOLE



CE STANDARD	ISO 20345:2004
CLASS	S3

UPPER	MATERIAL	SPECIFICATION
UPPER	CRAZY HORSE LEATHER	BROWN COLOR; THICKNESS: 2.2 MM, PH>3.5
VAMP LINING/QUARTER LINING	BROWN FUR+PERCALE	THICKNESS: 1MM, TEAR STRENGTH>15N
BOOT TUBE LINING	BROWN FUR+YARN	THICKNESS: 8MM+ - 1.5
BOOT TUBE LINING	STELLA	THICKNESS: 1MM, TEAR STRENGTH>15N
HEEL LINING	RED BRAN	BETWEEN UPPER AND LINING
INSOCKS	FUR+ 3MMINSOLE SLICE	
THREAD	BROWN AND WHITE COLOR	TEAR STRENGTH>50N
TOECAP	604 STEEL TOECAP	NO.10 TOECAP USED IN EU SZIE 41/42 ANTI-CORROSION IMPACT RESISTANCE >200J COMPRESSION RESISTANCE >1500KGS
BINDING OF TOE CAP	PC binding	THICKNESS: 3MM, VISCOSE/POLYESTER
SOLE COMPONENTS	MATERIALS	SPECIFICATION
INSOLE	ANTI-STATIC INSOLE	THICKNESS: 2.25MM WATER PERMEABILITY> 100MG/CM2
INSERT PLATE	STEEL INSERT PLATE	PENETRATION FORCE >1100N, ANTI-CORROSION
OUTSOLE	BI DENSITY POLYURETHANE	BLACK WEAR LAYER : 0,95 + 0,05 ABRASION RESISTANCE < 15 MM3 BENDING STRENGTH > 30000 UPPER/OUTSOLE ADHESION > 4 N / MM HEEL ENERGY ABSORPTION > 20 JOULES ANTI-SLIP FACTOR > SRC
SIZE	38-47	
WEIGHT	+/-600gr (one piece)	