

S3003 TECHNICAL SHEET

Model	S3003N
Series	Casual shoes

Description	
Low-top; Lace-up work shoes; Double density PU	
CE Standard	EN 13287
Category	SRA



UPPER COMPONENT	MATERIALS	SPECIFICATION
APRON+COUNTER	Black micro-fiber	Abrasion resistance and comfortable
UPPER	Black micro-fiber with pinhole	Comfortable and breathable, Tear strength > 60N
QUARTER LINING	Black K208 mesh	Abrasion resistance Tear strength > 15
VAMP LINING	Non-woven fabric	Thickness 1.3mm, gray-white Tear strength > 15N
COUNTER LINING	Black K208 mesh + foam + yarn	Foam thickness 4MM Tear strength > 15N
INSOCK	COFRA insole	Comfortable and shock absorption

SOLE COMPONENT	MATERIALS	SPECIFICATION
INSOLE	Anti-static insole	Thickness: 1.75MM, beige color
OUTSOLE	Black dual density PU outsole	Adhesion force between outsole and upper>4N/MM Heel-bearing capacity >20 J
SLIP RESISTANCE SRC	Test floor:suds+tile	Heel part friction index : 0.4 Flat contact friction index: 0.32
	Test Floor: Steel Floor +Glycerol	Heel part friction index :0.23 Flat contact friction index: 0.22
SIZE	35#-47#	
WEIGHT	+/-750g/pair	