

TECHNICAL SHEET

Model	S5001
Series	Toe protecting ,penetration resistance and anti-static shoes
Description	
HIGH-CUT BOOTS, BLACK STEEL TOECAP AND STEEL MIDSOLE DUEL DENSITY PU OUTSOLE	
CE Standard	EN ISO 20345:2011
Category	SIP SRC



UPPER COMPONENT	UPPER COMPONENT	SPECIFICATION
APRON+COUNTER	BLACK BARTON SPLIT BUFFALO LEATHER	THICKNESS : 1.8MM-2.0MM
COLLAR SURFACE	BLACK STELLA	
TONGUE SURFACE	BLACK STELLA	
TONGUE LINING/QUARTER LINING	LIGHT GREY D02 MESH COVERING 3MM SPONGE WITH YARN	WEAR-RESISTING AND PERMEABLE
COLLAR COTTON	SPONGE	THICKNESS: 15MM
QUARTER	HOT MELT COUNTER	THICKNESS: 1.5MM
INSOCK	GREY MESH COVERING 3MM EVA	WEAR-RESISTING AND PERMEABLE
THREAD	GREY 2*3, GREY 1*3	TENSILE STRENGTH >50N
TOE CAP	STEEL TOECAP	
BINDING OF TOE CAP	PLASTIC EDGEWISE	THICKNESS: 3MM, VISCOSE/POLYESTER

SOLE COMPONENTS	MATERIALS	SPECIFICATION
MIDSOLE	1.7MM BEIGE ANTI-STATIC INSERT PLATE	ANTI-STATIC
OUTSOLE	DUEL DENSITY PU OUTSOLE	ANTI-SLIP FACTOR >SRC
SIZE		
WEIGHT		