

## S5008 TECHNICAL SHEET

<b>Model</b>	S5008
<b>Series</b>	Safety shoes

<b>Description</b>
Low cut safety shoes with lacing; Composite toecap anti-smash and kevla insert plate anti-puncture; Dual density PU out-sole



<b>CE Standard</b>	EN ISO 20345:2011
<b>Category</b>	S1P SRC

UPPER COMPONENT	UPPER COMPONENT	SPECIFICATION
UPPER	Matte microfiber leather	Black, Thickness:1.8-2.0mm; Tear strength > 60N
APRON+COUNTER	Black matte microfiber leather with pinhole	Black, comfortable and breathable
QUARTER LINING	Grey canvas with bamboo charcoal cloth	Abrasion resistance and perspiration absorption Tear strength > 15N
VAMP LINING	Grey BK mesh	Abrasion resistance Tear strength > 15N
COUNTER LINING	Grey BK mesh + sponge + yarn	Sponge thickness 3MM Tear strength > 15N
INSOCK	Black mesh EVA + anti-static thread	Comfortable and shock absorption
TOE CAP	Composite toecap	Impact resistance>200J, Resistance to pressure >15KN

SOLE COMPONENT	MATERIALS	SPECIFICATION
INSOLE	LIKEKEVLA penetration resistance and Anti-static insole	Anti-penetration force >1100N
OUTSOLE	Black dual density PU out-sole	Shock absorption and flexing resistance Adhesion force between out-sole and upper>4N/MM Heel-bearing capacity >20 J
SLIP RESISTANCE SRC	Test floor: suds+tile	Heel part friction index: 0.4 Flat contact friction index: 0.32
	Test floor: suds+tile	Heel part friction index: 0.23 Flat contact friction index: 0.22
SIZE RANGE	35 - 47	
WEIGHT (Size: EUR 42)	1020g/pair (± 10g)	