



# **OIL & GUT RES**

# **PRODUCT**

Style No. 542 Material Nitrile

Liner 13-Gauge | Seamless

HPPE/Glass fiber

Size 7/S-11/XXL

Color Coating: Blue & Black, Liner: Gray

Size & Hem Color

8/M 9/L 10/XL 11/XXL

# where true reliability of the performance is needed. **FEATURES**

## **Maximum Performance**

**DESCRIPTION** 

A lightweight 13-gauge seamless HPPE liner and ergonomic design assures maximum comfort without decreasing the dexterity. The engineered design guarantees the maximum performance without fatigue.

The highest protection model of the series. Using the HPPE fiber technology,

In addition, ActivGrip™ Omega Max is designed for maximum liquid proof

protection, 360°. Combined with the liquid proof palm and MicroFinish® grip

technology, ActivGrip™ Omega Max is ideal for the most extreme tasks and

ActivGrip™ Omega Max achieves the high performance level in cut resistance.

# **Maximum Safety**

With using HPPE fiber, ActivGrip™ Omega Max offers the high cut resistant protection. Fingers are double coated to bring ActivGrip™ Omega Max to the highest level of safety without losing performance, durability and dexterity.

### Liquidproof Palm & Back

The double coated palm surface and coated back keep hands clean and prevents any liquids from outside. ActivGrip™ Omega Max combines maximum performance with hygiene for the ultimate protection of the user's hands.

### **Grip Performance**

Towa's original patented MicroFinish® technology offers the best grip in the industry in dry, wet and oily conditions.

# **GLOVE SERIES**





540 ActivGrip™ Omega

541 ActivGrip™ Omega Plus

# **Towa Corporation**

227 Tsubuku Honmachi, 830-0047 Kurume, Fukuoka, Japan Phone:+81-942-32-8863 Fax:+81-942-31-319

www.towagloves.com

### **TECHNICAL**







# **TECHNOLOGY**





### **APPLICATIONS**

Automotive / Assembly / Machine Operation Oily Material Handling / Glass Handling / Sheet Metal Handling

NBR MicroFinish Technology: U.S. Pat.No. 8,387,167 / EP Pat.No. 2143551 ZL200880010847.0



**DESIGN AND PERFORMANCE THAT WORKS**